

TRANSflo F

Automatic Transmission Fluid



Features & Benefits

- Corrosion & rust prevention
- Anti-foam characteristics
- Anti-wear
- Seal swell compatibility
- Low-temperature viscosity
- Sludge resistance

TRANSflo F is a niche ATF explicitly developed to meet the needs of Ford vehicles manufactured between 1950 and 1980. Ford formally approved it for applications requiring the M2C33-F specification. This fluid can also be used in power steering and hydraulic systems, especially in off-road construction and agricultural systems.

TRANSflo F, through extensive testing, has demonstrated dependable performance in the laboratory and the field. Industry tests include:

- Bench testing
- Clutch Friction Test
- Cycling Test
- Oxidation Testing
- Vickers Pump Testing

TRANSflo F is specified for the service fill in the following passenger car manufacturers: Austin-Morris, Saab, Daihatsu, Toyo Kogyo, Ford, Toyota, Jaguar, Triumph, Rover, and Volvo.

Specifications

✓ Meets Requirements

Specification	TRANSflo F
Volvo 97330	✓
Ford M2C33-F	✓
Ford M2C33-G	✓

Typical Results

Test Method	TRANSflo F
COLOUR	RED
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	35.6 7.4
VISCOSITY INDEX (D2270)	181
POUR POINT (D97) (°C)	-41
FLASH POINT (D93) (°C)	181
DENSITY @ 15 °C (D4052) (kg/L)	0.87

Sizes & Order Codes

Size	TRANSflo F
205 L / 54.2 Gal	F0109450
1000 L / 264 Gal	F0109460
Bulk	B0109401



www.irvingoil.com/lubricants
1.800.574.5823