

Waylube

Premium Slideway Lubricant



Features & Benefits

- Stops chatter, increasing machining accuracy
- Effective wear protection with EP and friction modifiers
- Excellent water and fluid separation
- Excellent adhesion, even on vertical surfaces

Waylube uses high quality paraffinic base oils with select additives to ensure a high-performance lubricant designed for use on the slide-ways of machine tools.

Waylube is formulated with extreme pressure (EP) agents that protect heavily loaded ways. Friction modifiers are added to reduce bonding between the metal surfaces, which stop stick-slip chatter.

Waylube contains a tackifier to help the oil adhere to metal surfaces, limiting fluid consumption by reducing leakage and being scraped away. This formulation also separates readily from water, resisting emulsification with water or coolants.

Waylube is non-corrosive to copper, bronze, and steel and will not stain these metals.

Typical Results

Test Method	Waylube 68	Waylube 220
ISO GRADE	68	220
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	66.3 9.3	220.5 19.8
DENSITY @ 15°C (D4052) (kg/L)	0.86	0.89
VISCOSITY INDEX (D2270)	118	103
FLASH POINT (D93) (°C)	202	204
POUR POINT (D97) (°C)	-15	-6

Size & Order Codes

Size	Waylube 68	Waylube 220
18.9L / 5 US gal Pail	F0082540	-
205L / 54.2 US Gal Drum	F0068950	F0021950
1000L / 264 US Gal Tote	F0022060	-
Bulk	B0022001	B0021901



www.irvingoil.com/lubricants
1.800.574.5823