

Form Oil Contractor



Features & Benefits

- Easy to use - can be painted or sprayed on
- Non-staining formula
- Protects metal and wooden forms
- Leaves a smooth surface

FORM OIL CONTRACTOR is a blend of quality pure paraffinic base oils and a fatty material to be used as a form-release agent with a rust-preventive coating.

FORM OIL CONTRACTOR is well suited especially in the manufacture of precast concrete structures, walls, pipe, curbs, and beams.

FORM OIL CONTRACTOR's viscosity allows it to be sprayed or brushed on. The light color of the fluid won't cause staining to the concrete.

FORM OIL CONTRACTOR is formulated with an added fatty material that reacts with the alkali in the cement to form a barrier between the form and the cement, helping them to separate easily while leaving the concrete with a smooth surface. This also protects wooden forms from tearing and will reduce the maintenance time needed to remove dried concrete from the form surface.

Typical Results

Test Method	FORM OILCONTRACTOR
VISCOSITY (D445) cSt @ 40°C	24.7
DENSITY @15°C (D4052), kg/L	0.85
ASTM COLOUR (D1500)	1.0
FLASH POINT (D93), °C	222
POUR POINT (D97), °C	-42

Sizes & Order Codes

Size	FORM OIL CONTRACTOR
18.9 L/ 5 US Gal	F0112240



www.irvingoil.com/lubricants
1.800.574.5823