



# FORM OIL

**FORM OIL** is a blend of quality pure paraffinic base oil and petroleum distillate, and is used as a form-release agent and rust-preventive coating.

## Features

- Easy to use — can be painted or sprayed on
- Low pour point for 3 season use
- Non-staining formula

## Benefits

- Effective
- Versatile — can be used as a general protective coating
- Leaves a smooth surface

For concrete form-work, the forms are coated with **FORM OIL** before being filled with concrete. The viscosity of **FORM OIL** allows it to be sprayed or brushed on and the light colour won't stain the concrete. A fatty material added to **FORM OIL** reacts with the alkali in the cement to form a barrier between the form and the cement that helps them to separate easily and leaves the concrete with a smooth surface. This also protects the wood forms from tearing and reduces the maintenance time needed to remove dried concrete from the form surface.

As a coating, **FORM OIL** helps prevent steel forms and machinery from rusting and prevents wood forms from absorbing water and rotting.



## Typical Performance Results

NAME	FORM OIL
VISCOSITY (D-445) cSt @ 40°C	2.5
POUR POINT (°C) (D-97)	-8
FLASH POINT (°C) (D-92)	70
DENSITY @ 15°C	0.824

## Available Package Sizes

### FORM OIL

- 20 L (5.28 US gal.) Pail
- 210 L (55.5 US gal.) Drum
- 500 L (132 US gal.) Cube
- 1000 L (264 US gal.) Cube
- Bulk

