



STALUBE

STALUBE oils are high-performance chain oils formulated especially for heavy-duty applications with chain saws and in industrial machinery where drippage is unwanted, unsightly or hazardous.

Unlike many chain oils, **STALUBE** is formulated using high quality paraffinic mineral base oils, not re-cycled or second-grade material, blended into 3 grades that are suitable for a wide range of operating conditions both in-plant and outdoors in any season. **STALUBE** is extremely tacky, which helps the oil stick where it is applied and resist drippage or throw-off, even from high-speed chains. This ensures unsurpassed protection and reduces consumption.

All grades (except 100) of **STALUBE** are dyed red to help operators check that there is enough lubricant on the chain. Un-dyed versions are also available.

STALUBE 40(W) is good for deep winter use, especially for the automatic chain lubricators on the heads of harvesters. This grade is formulated to maintain fluidity in extreme cold environments to -44C. **STALUBE 185** is suitable for chain saws outside in summer weather. This grade is formulated to maintain tackiness where lesser quality products tend to throw-off easily.

STALUBE 100 is a great lube for chainsaws in mid-season. It also can be used in outdoor/indoor automatic chain lubricators that require anti-wear protection.

STALUBE 320 is recommended for use in-plant on slow moving chains, pivots, hinges, plain bearings and wherever lubrication is needed that must resist drippage or where frequent re-lubrication is impractical.

Features

- High quality base oils
- Dyed for easy visibility
- Extremely tacky

Benefits

- Superior protection
- Multipurpose
- In-plant and outdoor compatible



Typical Performance Results

ISO GRADE	40(W)	100	185	320
COLOUR	RED	AMBER	DARK RED	DARK RED
VISCOSITY (D-445)				
cSt @ 40°C	40	100	185	320
cSt @ 100°C	7.1	12.3	18.0	26.0
VISCOSITY INDEX (D-2270)	139	113	109	108
POUR POINT (D-97) (°C)	-44		—	—
FLASH POINT (D-92) (°C)	220	264	294	297

Available Package Sizes

	946mL (1USqt)	3.78L (1USgal)	20L Pail (5.28USgal)	205L Metal (54.2USgal)	210L Drum (55.5USgal)	500L Cube (132USgal)	1000L Cube (264USgal)	Bulk
STALUBE 185 ND*			X	X	X	X		
STALUBE 185	X	X	X	X	X	X	X	X
STALUBE 320				X	X	X		X
STALUBE 40 ND*			X			X		
STALUBE 40	X	X	X		X	X	X	X
STALUBE 100				X				

Check with sales representative or website for the latest product approvals.

*ND: Non-Dyed product

