



# TRANSFLO® MULTI-VEHICLE

**TRANSFLO® MULTI-VEHICLE** is a premium synthetic blend transmission fluid designed to provide unparalleled severe duty operating performance in heavy duty transmissions.

Great resistance to oxidation and prevents the formation of gum or varnish in the transmission due to high temperature instability.  
Transflo Multi-Vehicle

## Features

**TRANSFLO® M-V** meets or exceeds the following standards:

- Mercon® V (approved)
- Voith extended drain
- ZF (TE-ML.14.B)
- Allison TES-295
- Allison C-4
- Caterpillar TO-2
- ATF +4, ATF +3 capable
- Suitable for use where Dexron® IIIH, IIIG, IIE, or II is recommended. Not suitable where Dexron® VI is required

**TRANSFLO® M-V** offers excellent fluidity at low temperature. It allows better cold lubrication and a faster starting. It has a very good thermal stability and an excellent protection against wear. It protects better and longer what reduces wear and extend the life of transmissions. It has a very good anti-corrosive and anti-foam characteristic. Its properties of friction ensure a better shifting of speed, eliminates vibration with the clutch and speed shifting.

**TRANSFLO® M-V** is Mercon® V approved. It is also suitable for use in transmissions where ATF +4, ATF +3, Voith, ZF. It can also be used in transmissions where Dexron III-H, III-G, & II are required.

**TRANSFLO® M-V** may also be used as a hydraulic or power steering fluid.

## Benefits

- Maximum value service life in heavy duty fleets- up to 100,000 miles or 50,000 miles in severe duty as recommended by OEM's
- Exceptional low temperature fluidity
- Excellent resistance to degradation due to heat and oxidation
- Eliminates slippage and shudder
- Extends integrity and operational life of critical components



## Typical Performance Results

COLOUR	Red
DENSITY, KG/L @ 15°C(60°F) D-4052	0.854
VISCOSITY D-445 cSt @ 40°C (SUS @ 100°F) cSt @ 100°C (SUS @ 210°F)	34.0 (171) 7.6 (51.3)
VISCOSITY INDEX D-2270	203
BROOKFIELD VISC. D-2983 cP @ -40°C (-40°F)	10,500
POUR POINT °C (°F) D-97	-49 (-56)
FLASH POINT °C (°F) D-92	186 (367)

## Available Package Sizes

	473mL (1 US pint)	946mL (1 US quart)	3.78L (1 US gal)	20L Pail (5.28 US gal)	205L Drum (54.2 US gal)	210L Drum (55.5 US gal)	500L Cube (132 US gal)	1000L Cube (264 US gal)	Bulk
<b>TRANSFLO® M-V</b>		X	X	X		X	X	X	X

Check with sales representative or website for the latest product approvals.

