



# MATERIAL SAFETY DATA SHEET

## SECTION 1 - PRODUCT IDENTIFICATION AND USE

**Product Name:** Waylube (All)  
**Product Class:** Lubricant  
**WHMIS Classification:** Not Controlled.

**Supplier Name and Address:** COASTAL Blending & Packaging  
P.O. Box 1169  
Saint John, N.B.  
E2L 4E6

**Phone:** (800) 574-5823  
**Emergency:** (506) 648-3060

## SECTION 2 - HAZARDOUS INGREDIENTS OF MATERIALS

<u>Hazardous Ingredients</u>	<u>CAS#</u>	<u>wt%</u>	<u>ACGIH-TLV</u>	<u>LC<sub>50</sub></u>	<u>LD<sub>50</sub></u>
None			5 mg/m <sup>3</sup> (oil mist)		

## SECTION 3 - PHYSICAL DATA AND CHEMICAL PROPERTIES

<b>Form:</b>	Liquid	<b>Vapour Pressure (mm @ 20°C):</b>	< 0.10
<b>Colour:</b>	Light to Dark Brown	<b>Volatile (wt%):</b>	0
<b>Odour:</b>	Pungent		
<b>Specific Gravity @ 15°C:</b>	0.89 - 0.90		
<b>Solubility:</b>	Negligible		

## SECTION 4 - FIRE AND EXPLOSION HAZARD

**Flammability:**  Yes  No  
**Flash Point :** > 230°C (COC)

**Conditions:** Open flame above flash point.

**Upper Flammable Limit:** Not established.  
**Auto Ignition Temperature:** Not determined.  
**Sensitivity to Impact:** None.

**Lower Flammable Limit:** Not established.  
**TDG Flammability Classification:** Not classified.  
**Sensitivity to Static Discharge:** None.

**Means of Extinction:** Dry chemical, water spray (fog), foam or carbon dioxide.  
**Hazardous Combustion Products:** Hydrogen sulphide and oxides of carbon, nitrogen, sulphur and phosphorus.  
**Special Procedures:** Water foam may cause frothing. Use water to cool exposed containers. Use self-contained breathing apparatus for fire fighting.

## SECTION 5 - REACTIVITY DATA

**Stability:** This product is stable.  
**Hazardous Polymerisation:** Will not occur.  
**Conditions to avoid:** Extremely high temperatures.  
**Incompatibility with other substances:** Strong oxidising agents.  
**Hazardous decomposition products:** Thermal decomposition from high temperature or combustion will produce hydrogen sulphide and oxides of carbon, nitrogen, sulphur and phosphorus.

## SECTION 6 - TOXICOLOGICAL PROPERTIES

**Route of Entry:**  Eye  Skin Contact  Skin Absorption  Inhalation  Ingestion

**Effects of Acute Exposure:** Irritation to skin and eyes. Inhalation of hot oil mist or vapours may irritate the upper respiratory tract.  
**Effects of Chronic Exposure:** Repeated or prolonged exposure may cause dermatitis and/or oil acne. Long-term intensive exposure to oil mist may cause benign lung fibrosis. No specific toxicity data but extrapolation from similar materials indicates that this product has low oral toxicity.

<b>Exposure Limits:</b>	5 mg/m <sup>3</sup> (oil mist)	<b>Carcinogenicity:</b>	Not determined.
<b>Reproductive Toxicity:</b>	Not determined.	<b>Teratogenicity:</b>	Not determined.
<b>Irritancy of Product:</b>	Slight.	<b>Mutagenicity:</b>	Not determined.

The information contained in this form is based on data from sources considered to be reliable but COASTAL Blending & Packaging does not guarantee the accuracy or completeness thereof. The information is provided as a service to the persons purchasing or using the material to which it refers and COASTAL Blending & Packaging expressly disclaims all liability for loss or damage including consequential loss or for injury to persons including death. The information shall not be reproduced, published or distributed in any manner without prior consent in writing of COASTAL Blending & Packaging



# MATERIAL SAFETY DATA SHEET

---

## SECTION 7 - PREVENTATIVE AND CORRECTIVE MEASURES

---

**Personal Protective Equipment:** *Gloves:* Oil/Chemical resistant.  
*Eye:* Chemical safety glasses or full face shield.  
*Respiratory:* NOISH respirator if mist levels are high.  
*Footwear:* Oil/Chemical resistant.  
*Clothing:* Oil/Chemical resistant if repeated exposure to skin and clothing occurs.  
*Other:*

**Engineering Controls:** Local exhaust at source of heated vapours.

**Leak and Spill Procedure:** Contain spills with dikes or absorbent material. Eliminate fire hazards. Prevent from entering sewers or water courses. Vacuum liquid or transfer absorbed material into containers. Advise authorities.

**Waste Disposal:** Follow local and governmental regulations. Not regulated as a hazardous waste.

**Storage Requirements:** Cool, dry location. Keep containers closed.

**Special Shipping Information:** No special requirements.

---

## SECTION 8 - FIRST AID MEASURES

---

**Inhalation:** Remove to fresh air or give artificial respiration. If breathing is difficult, give oxygen and seek medical attention.

**Ingestion:** Do not induce vomiting, give two glasses of water and seek medical attention.

**Eye:** Flush with water for 15 minutes.

**Skin:** Wash contaminated area with soap and water. Clean contaminated clothing before wearing again.

**General Advice:** High pressure injection under skin can be serious and requires urgent medical attention.

---

## SECTION 9 - PREPARATION DATE OF MSDS

---

**MSDS Prepared by:** COASTAL Blending & Packaging      **Phone:** (800) 574-5823  
**MSDS Date:** January 11, 2010  
**Revision** 02