

# Form Oil Contractor

## Features & Benefits

- Easy to use
- Can be painted or sprayed on
- Non-staining formula
- Protects metal
- Leaves a smooth surface



**FORM OIL CONTRACTOR** is a blend of quality pure paraffinic base oil and a fatty material to be used as a form-release agent with a rust-preventive coating.

**FORM OIL CONTRACTOR** is well suited especially in the manufacture of precast concrete structures, walls, pipe, curbs, and beams.

**FORM OIL CONTRACTOR's** viscosity allows it to be sprayed or brushed on and the light color won't stain the concrete. A fatty material added to the formula reacts with the alkali in the cement to form a barrier between the form and the cement that helps them to separate easily and leaves the concrete with a smooth surface. This also protects wood forms from tearing and reduces the maintenance time needed to remove dried concrete from the form surface.

## Sizes & Order Codes

FORM OIL CONTRACTOR
18.9L / 5 US Gal F0112240

## Typical Characteristics

NAME	FORM OIL CONTRACTOR
<b>VISCOSITY</b> (D445) cSt @ 40°C	26.4
<b>DENSITY @15 (°C)</b> (D4052) Kg/L	0.8534
<b>ASTM COLOUR</b> (D1500)	1.5



Blending & Packaging

www.irvingblend.com  
1.800.574.5823

Supporting data available to demonstrate appropriate performance.  
Check with your Sales Representative for latest product approvals.  
Please note, these are typical performance indicators and can change without notice.  
This data sheet supersedes any previous version prior to 07/07/2018.