

Form Oil



Features & Benefits

- Easy to use — can be painted or sprayed on
- Low pour point for 3 season use non-staining formula
- Effective
- Versatile — can be used as a general protective coating
- Leaves a smooth surface

FORM OIL is a blend of quality pure paraffinic base oil and petroleum distillate and is used as a form-release agent with a rust-preventive coating.

FORM OIL works with concrete form-work coated with this oil before being filled with concrete.

FORM OIL's viscosity allows it to be sprayed or brushed on and the light color won't stain the concrete. A fatty material added to the formula reacts with the alkali in the cement to form a barrier between the form and the cement that helps them to separate easily and leaves the concrete with a smooth surface. This also protects wood forms from tearing and reduces the maintenance time needed to remove dried concrete from the form surface.

FORM OIL as a coating helps prevent steel forms and machinery from rusting and prevents wood forms from absorbing water and rotting.

Sizes & Order Codes

Form Oil
18.9L F0084440
205L F0003850
1000L (264 US Gal) F0003860
Bulk B0003801

Typical Characteristics

NAME	FORM OIL
VISCOSITY (D445) cSt @ 40°C	6.0
DENSITY @15 (°C) (D4052) Kg/L	0.8455
POUR POINT (°C) (D97)	-8
FLASH POINT (°C) (D92)	65



Blending & Packaging

www.irvingblend.com
1.800.574.5823

Supporting data available to demonstrate appropriate performance.
Check with your Sales Representative for latest product approvals.
Please note, these are typical performance indicators and can change without notice.
This data sheet supersedes any previous version prior to 6/18/2018.