

# TRANSflo F

## Automatic Transmission Fluid



### Features & Benefits

- Corrosion & rust prevention
- Anti-foam characteristics
- Anti-wear
- Seal swell compatibility
- Low temperature viscosity
- Sludge resistance
- Meets the following: Volvo 97330, Ford M2C33-F
- Specified for the service fill in the following passenger car manufacturers: Austin-Morris, Saab, Daihatsu, Toyo Kogyo, Ford, Toyota, Jaguar, Triumph, Rover, Volvo

**TRANSflo F** is a niche ATF developed specifically to meet the needs of Ford vehicles manufactured between 1950 and 1980. It was formally approved by Ford for specifications M2C33. This fluid can also be used in power steering and hydraulic systems, especially in off road construction and agricultural systems.

**TRANSflo F** through extensive testing has demonstrated dependable performance in the laboratory and the field includes the following industry tests:

- Bench testing
- Clutch Friction Test
- Cycling Test
- Oxidation Testing
- Vickers Pump Testing

### Sizes & Order Codes

TRANSflo F
1000L / 264 US Gal F0109460
Bulk B0109401

### Typical Results

COLOUR	Red
<b>VISCOSITY (D445)</b> cSt @40°C	35.6
cSt @ 100°C	7.4
<b>VISCOSITY INDEX (D2270)</b>	181
<b>DENSITY @ 15°C (D4052), Kg/L</b>	0.8659
<b>FLASH POINT (°C) (D93)</b>	181
<b>POUR POINT (°C) (D97)</b>	-41



Blending & Packaging  
www.irvingblend.com  
1.800.574.5823

Supporting data available to demonstrate appropriate performance.  
Check with your Sales Representative for latest product approvals.  
Please note, these are typical performance indicators and can change without notice.  
This data sheet supersedes any previous version prior to 12/05/2018.