

# TRAX MV 20W50

## Multi-Vehicle Engine Oil



### Features & Benefits

- Designed for engines with the warranty requirements of API SL/CF and JASO MA2
- Great wet clutch performance and protection
- Reduces engine friction
- Great high RPM / high temperature protection
- Helps prevent sludge and other damaging deposits from forming
- Provides excellent protection over a wide temperature range
- Oxidation and shear stability resistance

### Specifications

Meets Requirements Of:	20W-50
API SL/CF	✓
JASO MA2	✓

### Sizes & Order Codes

TRAX MV 20W-50
946 ml/1 US Qt. FEE0005415

### Typical Results

TRAX MV 20W-50	20W50
DENSITY @ 15°C (D4052) (kg/L)	-
VISCOSITY (D445) cSt @ 40 °C cSt @ 100 °C	142.3 18.5
VISCOSITY INDEX (D2270)	146
POUR POINT (°C) (D97)	-30
FLASH POINT (°C) (D93)	211



**TRAX MV 20W-50** engine oil is blended with high quality base oils and additive technology to help achieve peak performance in high-demand engine applications. This versatile engine oil gives excellent protection over a wide temperature range and high RPM while reducing engine friction.

**TRAX MV 20W-50** engine Oil provides improved shear stability, great oxidation resistance and optimal wet clutch performance and protection.

**TRAX MV 20W-50** engine oil is designed for engines with the warranty requirements of API SL/CF and JASO MA2 and is suitable for use in all Japanese and European motorcycles where a SAE 20W-50 JASO MA2 oil is required.



[www.irvingblend.com](http://www.irvingblend.com)  
1.800.574.5823

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 02-12-19.

[www.irvingblend.com](http://www.irvingblend.com) 1.800.574.5823