



# TRANSflo MV

Multi Vehicle

## Features & Benefits

- Exceptional low temperature fluidity
- Excellent resistance to degradation due to heat and oxidation
- Eliminates slippage and shudder
- Extends integrity and operational life of critical components
- MERCON® -V approved
- Suitable for use in most transmissions, this is a true multi vehicle fluid



Irving TRANSflo MV was designed to meet the performance requirements of global transmissions from North American, European and Asian transmission manufactures.

Irving TRANSflo MV offers excellent fluidity at low temperatures allowing for better lubrication and faster start times in extremely cold temperatures.

Irving TRANSflo MV protects better and longer than previous automatic transmission fluids to reduce wear and extend the durability of the transmission. The friction properties ensure smoother, shudder-free shifting and eliminates vibration within the clutch; even when speed shifting.

Irving TRANSflo MV may also be used as a hydraulic or power steering fluid.

## Specifications

Meets the requirements of

High Viscosity Specifications
Acura ATF-Z1
Aisin Warner JWS 3309 (T-IV)
Allison C-3 & C-4
American Motors ATF +3 (MS 7176E)
ATF RED1, RED1K
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)
Audi G 052 162-A1/A2
Audi G 052 025-A2
Audi/VW G 052 990
Audi G 052 055
Audi G 053 025-A2
Audi G 055 025 A2 (JWS 3309)
AW-1
Bosch TE-ML 09
BMW JWS 3309 (T-IV)
BMW LA2634
BMW 7045E
BMW ETL-8072B
BMW MINI
CAT TO-2
Chrysler ATF+2, ATF+3 (MS 7176E)
Chrysler/Dodge MOPAR AS 68 RC (T-IV) JWS 3309
Daewoo LT 71141
Daihatsu AMMIX ATF D-II, D-III SP
Daihatsu Friend ATF D-III
Esso LT 71141
FIAT T-IV Type JWS 3309
Ford MERCON®
Ford MERCON®-V
Ford FNR5
Ford M2C138CJ
Ford M2C166H
Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309
Fuso ATF-II
Fuso ATF-SP II
Fuso ATF- A4
GM9986195 (Aisin AW, JWS 3309)
GM TASA
GM DEXRON® II, DEXRON® IID, DEXRON® IIE, DEXRON® IIIG, DEXRON® IIH

High Viscosity Specifications
Hino Blue Ribbon ATF
Honda ATF- Z1 (not for use in CVT)
Honda ATF Ultra II
Honda DW-1
Hyundai/Kia Dex-II/SP-II
Hyundai/Kia SP-III
Hyundai/Kia JWS 3314
Hyundai/Kia JWS 9683
Hyundai/Kia 040000C90SG
Idemitsu K17
ISUZU BESCO ATF SP
ISUZU SCS Fluid
ISUZU 08200-9001
ISUZU BESCO ATF-II, BESCO ATF-III
Jaguar ATF 3403 M115
Jaguar ATF LT71141, ZF 5HP24
Jaguar JLM 20292
Jaguar JLM 21044
Jaguar Fluid 8432
JASO M315-2013 1A
JASO MS315-2013 2A
JEEP ATF +3
Lexus JWS 3309
KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1
Mazda ATF D-II
Mazda ATF M-III, ATF M-V
Mazda ATF F-1
Mazda ATF S-1
Mazda ATF N-1
Mazda ATF 3317
Mini Cooper T-IV
Mitsubishi Diaqueen SK
Mitsubishi Diaqueen SP-II, SP-III
Mitsubishi Diaqueen AW
Mitsubishi Diaqueen J2
NAG 1 (Chrysler, Jeep, Cherokee)
Nissan Matic Fluid C
Nissan Matic Fluid D
Nissan Matic Fluid J
Nissan Matic Fluid K
Nissan Matic Fluid N4
Opel

## Sizes & Order Codes

TRANSflo MV	
946 ml/ 1 US Qt.	F0076315
60 L/ 15.85 US Gal	F0076345
205 L/ 54.2 US Gal	F0076350
Bulk	B0076301

## Typical Results

Test Method	TRANSflo MV
COLOUR	RED
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	34.0 7.6
VISCOSITY INDEX (D2270)	202
DENSITY @ 15 °C (D4052) kg/L	0.85
BROOKFIELD VISCOSITY (D2983) cP @ -40°C	9,580
POUR POINT (°C) (D97)	-48
FLASH POINT (°C) (D92)	214

[www.irvingblend.com](http://www.irvingblend.com)  
1.800.574.5823

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 04-10-19.

[www.irvingblend.com](http://www.irvingblend.com) 1.800.574.5823

# TRANSflo MV

## Multi Vehicle

### Specifications Continued

Meets the requirements of

High Viscosity Specifications
Peugot/Citreon Z 000169756
Porsche T-IV (JWS 3309)
Renault Samsung SATF-D
Ssang young DSIH 5M-66
Saab T-IV (JWS 3309)
Saturn T-IV (JWS 3309)
Scion
Subaru ATF
Subaru ATF for Vivio 3 speed
Subaru ATF 5AT
Subaru ATF, ATF HP
Subaru K0140Y0700
Suzuki AT OIL 5006
Suzuki ATF 2326
Suzuki ATF 2384K
Suzuki ATF 3309
Suzuki ATF 3314
Suzuki ATF 3317
Suzuki ATF AW-1
Texaco 7045-E
Texaco 8072B
Texaco N402
Toyota ATF D-II, ATF D-III
Toyota ATF T-III, ATF T-IV
Vickers M2950-S, I-286-S
Volvo CE 97340
Volvo 97325
Volvo 97335
VW G US 000 162
VW G-055-025 A2 (JWS 3309)
ZF-TE-ML 05L
ZF-TE-ML 09
ZF-TE-ML 11A, 11B
ZF TE-ML 21L

Low Viscosity Specifications
Honda DW-1
Hyundai/Kia SP-IV
Hyundai/Kia SP-IV M
Hyundai/Kia SP-IV RR
Hyundai/Kia NWS 9638
JWS 3324 (WS)
Mazda ATF FZ
Mitsubishi Diaqueen SP-IV
Mitsubishi Diaqueen J3
Mitsubishi Diaqueen ATF PA
Nissan Matic Fluid S
Saab 93 165 147
Toyota ATF WS

Transfer Case Applications
Ford MERCON®-V
Ford Part#XL-12
GM IID, IIH

Power Steering Applications
Chrysler MS-1872
Chrysler MS 5931
Chrysler MS 9602
Ford M2C195-A
GM P/N 89021184
GM P/N 1052884 (GM 9985010)
GM P/N 12345866 (GM 9985835)
Hyundai/Kia PSF-3
Mercedes-Benz 236.3 (P/N 000 989 88 03)
Mitsubishi PS fluid, Diamond SP-III
Nissan PSF-II
Saab P/N 45 30 09 800
Subaru P/N K0209A0080
ZF TE-ML 09



Always consult your owner's manual for verification of fluid type and grade!

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 04-10-19.

[www.iringblend.com](http://www.iringblend.com) 1.800.574.5823