



# TRANSflo



## Features & Benefits

- Excellent corrosion and foam prevention
- Safe for all seals
- Promotes transmission cleanliness

**Irving TRANSflo** is a premium product specially formulated for use in automatic transmissions manufactured in 2005 and earlier for General Motors, Ford, and Chrysler vehicles.

**Irving TRANSflo** provides excellent low temperature fluidity as well as good viscosity at temperatures in excess of 149°C for bearing and gear lubrication.

**Irving TRANSflo** meets specifications by Allison as a type C-4 fluid and can be used in Ford model C-6 automatic transmissions built on or after 1977.

**Irving TRANSflo** can also be used in some power steering, hydro-static systems and power-shift transmissions where this type of oil is recommended.

**Irving TRANSflo** may also be used as hydraulic fluid due to it's excellent low temperature fluidity and red color.

## Specifications

Meets Requirements Of
Allison C-3 & C-4
Allison TES-389
American Motors ATF +3 (MS 7176-E)
Audi G 052 162-A1/A2 (ZF Lifeguard 5)
BMW 7045E
BMW ETL-8072B
BMW LA2634
CAT TO-2
Chrysler ATF+2, +3
Ford MERCON®
Ford WSS M2C 183CJ, 166H
GM DEXRON®II
GM DEXRON®IID
GM DEXRON®IIE
GM DEXRON®IIIG
GM DEXRON®IIIH
GM TASA
Hyundai/Kia DEX-II/SP-II
Jaguar JLM 20292
Jaguar JLM 20238
Mazda ATF M-III
Mazda ATF F-I
MB ZF 4HP20
NAG 1 (Chrysler, Jeep, Cherokee)
Opel/GM 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466
Peugot/Citreon Z 000169756, AL4 Automatic gearbox oil (#9730.AE)
Porsche 000 043 205 09, 999 917 547 00, Z 000169756
Renault Matic D2
Renault DPO/AL4
Volvo CE 97340
Volvo 97325
Volvo 97335
Vickers M2950-S, I-286-S
VW G US 000 162
ZF TE-ML 05L
ZF TE-ML 09
ZF TE-ML 21L

## Sizes & Order Codes

TRANSflo
946mL/1 US quart F0020815
3.78L/ 1 US gal F0020826
18.9L Pail/ 5 US gal F0082240
205L Drum/ 54.2 US gal F0015650
1000L Cube/ 264 US gal F0020860
Bulk B0020801

## Typical Results

Test Method	TRANSflo
<b>COLOUR</b>	RED
<b>VISCOSITY</b> (D445) cSt @ 40°C cSt @ 100°C	33.2 7.1
<b>VISCOSITY INDEX</b> (D2270)	186
<b>POUR POINT</b> (D97) (°C)	-42
<b>FLASH POINT</b> (D93) (°C)	190
<b>DENSITY</b> (D4052) kg/L	0.85

[www.irvingblend.com](http://www.irvingblend.com)  
1.800.574.5823

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 04-10-19.

[www.irvingblend.com](http://www.irvingblend.com) 1.800.574.5823