



# Syn Trax

## Synthetic Blend 2-Stroke Engine Oil

### Features & Benefits

- Ensures higher engine protection, limits deposits on pistons and segments
- Pours easily at temperatures as low as -38°C
- Prevents rust and corrosion, minimizes ring-sticking, port plugging and pre-ignition
- Less fumes escape
- Releases a pleasant vanilla scent



**Syn Trax** is a synthetic blend lubricant for 2-stroke engines. The synthetic components improve lubricity while providing cooler and more efficient combustion resulting in reduction of smoke which prevents exhaust port deposits and blockage. It has been formulated with snowmobiles in mind, both air and liquid-cooled where the manufacturer recommends a low-ash oil. It meets the stringent requirements of Bombardier® snowmobiles and is power valve optimized. Formulated to provide superior protection for high-performance 2-stroke engines.

**Syn Trax** prevents deposits on pistons, thereby providing a higher level of lubrication and reducing wear and failure. You can increase the lifespan of your engine and have better protection under heavy loads and high temperatures with this premium oil. Enjoy your ride with reduced smoke emissions and a pleasant vanilla scent.

**Syn Trax** can be used in oil-injected or pre-mixed systems with a ratio of up to 100:1. This oil is suitable for chain saws, including professional models, as well as string trimmers, lawnmowers, snow blowers, motorcycles, ATVs and any other air-cooled 2-stroke gasoline engine. For water-cooled outboard engines, consider using **Irving 2-Cycle Plus**.

### Specifications

Meets requirements of:	
JASO FB, FC, FD	
ISO-L-EGB, EGC, EGD	
API TC	
Meets the requirements of manufacturers including:	
Bombardier	
Arctic Cat	
Polaris	
Yamaha	

### Sizes & Order Codes

Syn Trax	
946 ml/1 US Qt F0070315	

### Typical Results

Product	SYN TRAX
VISCOSITY (D445) cSt @ 40 °C cSt @ 100 °C	53.2 8.5
VISCOSITY INDEX (D2270)	135
POUR POINT (°C) (D97)	-40
FLASH POINT (°C) (D93)	99
DENSITY @ 15°C (ASTM D4052) kg/L	0.87

[www.irvingblend.com](http://www.irvingblend.com)  
1.800.574.5823

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 12-10-2018.

[www.irvingblend.com](http://www.irvingblend.com) 1.800.574.5823