

BIO-HYDRAULIC Premium Biodegradable Hydraulic Oil

IRVING

Irving Bio-Hydraulic 46 is a premium environmentally responsible hydraulic fluid engineered to provide exceptional performance in hydraulic and circulation systems.

Irving Bio-Hydraulic 46 satisfy the requirements for ultimate biodegradability and non-toxicity making it an excellent choice for hydraulic and circulation systems operating in environmentally sensitive areas.

Irving Bio-Hydraulic 46 meets or exceeds most major hydraulic pump and system manufacturer's toughest fluid requirements. It contains anti-wear and film strength additives for hydraulic systems operating under high load and high-pressure settings. It also provides excellent protection against rust and corrosion.

Irving Bio-Hydraulic 46 complies with the "biodegradable", "minimally-toxic" and "not bio-accumulative" standards as defined in Appendix A of the 2013 Vessel General Permit issued by the United States Environmental Protection Agency.

Sizes & Order Codes

Bio-Hydraulic 46

18.9L (5.0 US Gal)

F0123540

www.irvingoil.com/lubricants 1.800.574.5823

Features & Benefits

- · Readily biodegradable
- Excellent choice for hydraulic and circulation systems operating in environmentally sensitive areas

Specifications

Meets or Exceeds manufactures and industry test standards		
Bio-degradation ASTM D5864	Ultimate Biodegradable	
Classification	Pw1	

Typical Results

ISO Grade	46
Density @ 15°C (D4052), kg/l	0.876
Viscosity (D445) cSt @ 40°C cSt @ 100°C	43.8 9.7
Viscosity Index (D2270)	215
Pour Point (D97), °C	-38
Flash Point (D92), °C	243
Fire Point (D92), °C	266
4-Ball Wear, mm	0.35
FZG Gear Test	12
Emulsion Tendency	40/40/0 10 min
Biodegradation Classification	Ultimate Pw1
VGP/EAL Compliant	Yes