



# Advant

## Ultra High Performance Full Synthetic European

### Features & Benefits

- Robust engine performance
- Exceptional wear and sludge protection
- Excellent piston cleanliness

### Specifications

Meets Requirements Of:	5W-30	5W-40
API SN/CF	-	✓
API SL/CF	✓	✓
ACEA A3/B3	✓	✓
ACEA A3/B4	✓	✓
ACEA A5/B5	✓	-
JASO MA-2	✓	✓
MB 226.5	✓	✓
MB 229.3	✓	✓
MB 229.5	✓	-
VW 502.00/505.00	✓	✓
RN 0710/RN 0700	✓	✓
Porsche A40	-	✓

### Sizes & Order Codes

Sizes	5W-30	5W-40
946 ml/1 US Qt.	F0096006	F0000206
5 L/1.32 US Gal	N/A	F0000230
60 L/15.8 US Gal	F0096045	F0000245
205 L/54.2 US Gal	F0096050	F0000250
1000 L/264 US Gal (Bulk Tote)	F0096001	F0000201

### Typical Results

SAE Grade	5W-30	5W-40
<b>DENSITY @ 15°C (D4052) (kg/L)</b>	0.85	0.85
<b>VISCOSITY (D445)</b>		
cSt @ 40 °C	68.8	84.6
cSt @ 100 °C	11.8	14.1
<b>VISCOSITY INDEX (D2270)</b>	168	173
<b>POUR POINT (°C) (D97)</b>	-36	-36
<b>FLASH POINT (°C) (D93)</b>	211	214
<b>TOTAL BASE NUMBER (D2896) (mg KOH/g)</b>	10.24	10.34
<b>COLD CRANK (D5293) cP@-30(°C)</b>	5365	6389



**ADVANT** 100% synthetic passenger car motor oil offers the ultimate in lubricant protection for European gasoline and diesel powered automobiles.

**ADVANT** is no ordinary motor oil, it is a sophisticated formula of pure and stable base stocks coupled with the latest in additive technology. This formulation will deliver the performance and protection your engine demands.

**ADVANT** was formulated to keep your engine as close as possible to factory cleanliness. The tighter the clearances in your engine the cleaner you need to run, even a small deposit can make a major difference in performance.

**ADVANT** has excellent cold-start protection circulating quickly to create a protective film for vital engine components. When used in extreme high temperatures this protection reduces wear, resists oxidation and retains viscosity stability to extend engine service life.

*\*Although long life is a feature of the stability of synthetic oils, the engine manufacturers' oil drain intervals should always be respected.*



[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants)  
1.800.574.5823

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to December 2, 2021

[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants) 1.800.574.5823