

HT 70

Economical Flushing / Circulating



Features & Benefits

- Light yellow
- Good stability
- Economical
- Versatile
- High flash point
- Flushing oil

Typical Results

TEST METHOD	HT 70
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	9.0 Typ. 2.3 – 2.7
VISCOSITY INDEX (D2270)	≥ 90
POUR POINT (°C) (D97)	≤ -30
FLASH POINT (°C) (D92)	≥ 170
COLOR (D1500)	≤ 1.0
DENSITY (D4052) kg/L @15°C	0.815 – 0.85

Size & Order Codes

SIZE	HT 70
18.9L / 5.0 US gal Pail	F0087340
205L / 54.2 US gal Drum	F0012750
1000 L / 264 US Gal Tote	F0005860



HT 70 is formulated using pure high-quality paraffinic base oils with a good natural viscosity index (VI) with clear, light yellow colour.

HT 70's neutral nature provides for naturally low corrosive tendencies.

HT 70 is ideal for band-saw lubrication in sawmills. It is a far safer alternative to diesel fuels, heating oil, stove oil or kerosene, in this application. It can be wicked or sprayed and will significantly reduce consumption compared to fuels.

HT 70 is recommended for use as flushing oil and as a lubricant wherever light oil is required, such as pneumatic devices, high speed bearings, spindles and anywhere that a once-through product is called for that does not require anti-wear, extreme pressure or other performance enhancing additives.



www.irvingoil.com/lubricants
1.800.574.5823