

Universal Tractor Fluid



Recommended where fluids meeting the following and other, specifications:

- Cost effective performance
- Excellent field performance in a variety of tractors and equipment
- Superior final drive performance
- Excellent cleanliness
- Superior pump wear & abrasion protection
- Enhanced friction durability
- Caterpillar TO-2 (Suitable for Use)
- CNH MAT 3525 (Suitable for Use)
- John Deere J20A (Suitable for Use)
- John Deere J20B (Suitable for Use)
- John Deere J20C (Meets)
- John Deere J20D (Meets)
- MF M1145 (Suitable for Use)

Cobra UTF (Universal Tractor Fluid) is a multi-application lubricant used to lubricate the moving parts of off-highway mobile equipment. These fluids are used to lubricate the transmissions, differentials, final drive planetary gears, wet brakes and hydraulic systems of farm tractors and construction equipment that have a common fluid reservoir calling for a combination lubricant and power transmission fluid. The properties of these products provide unique characteristics since the same fluid must lubricate the transmission as well as the final drive, actuate hydraulic type disc brakes which are submerged in oil, and serve as a hydraulic fluid to operate power steering units, power take-offs, implements and attachments.

Cobra UTF has been formulated to provide a cost effective fluid without sacrificing performance. They offer excellent low temperature fluidity, which is helpful to construction equipment that must work in winter, as well as high temperature protection.

Cobra UTF is compatible with manufacturers' fluids and competitors' fluids of this type.

Typical Characteristics

GRADE NAME	UTF
VISCOSITY (D-445) cST @ 40 °C	62.4
cST @ 100 °C	10.1
VISCOSITY INDEX (D-2270)	148
POUR POINT (°C) (D-97)	-36
FLASHPOINT (D-92) (°C)	225

GRADE NAME	18.9L (5 US Gal)	205L Drum (54.15 US Gal)	1000L Cube (264 US Gal)	Bulk
UTF	FBB0008440	FB0008450	FBB0008460	BB0008401