



*"Give some bite to
your engine!"*

Cobra Saw Guide Oil

Features and Benefits

- Extremely tacky
- Dye free
- Resists throw-off and reduces consumption
- Helps extend blade life

Cobra Saw Guide Oil has been formulated for heavy-duty use on saw blades and guides in mill applications.

Cobra Saw Guide Oil is extremely tacky, which helps the oil stick to the surface and resist drippage or throw-off.

Cobra Saw Guide Oil is good for winter use, especially for the automatic chain lubricators on the heads of harvesters. This grade is formulated to maintain fluidity in extreme cold environments to -45°C.



Typical Results

TEST METHOD	SAW GUIDE OIL
ASTM COLOUR (D1500)	3.5
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	64.3 10.9
VISCOSITY INDEX (D2270)	161
FLASH POINT (°C) (D93)	183
POUR POINT (°C) (D97)	-45

Sizes and Order Codes

SIZE	SAW GUIDE OIL
3.78L 1 US Gal	N/A
18.9L / 5 US Gal	N/A
205L / 54.2 US Gal	N/A
1000L / 264 US Gal	FBB0010460



Supporting data available to demonstrate appropriate performance. Check with your Sales Representative for latest product approvals. Please note, these are typical performance indicators and can change without notice. This datasheet supersedes any previous version prior to May 3, 2022.

www.irvingoil.com/en-CA/blending-packaging/cobra for more information