

# Form Oil



## Features & Benefits

- Easy to use – can be painted or sprayed on
- Low pour point for 3 season use non-straining formula
- Effective
- Versatile – can be used as a general protective coating
- Leaves a smooth surface

## Typical Results

Test Method	Form Oil
<b>VISCOSITY</b> (D445) cSt @ 40°C	6.0
<b>DENSITY @15 (°C)</b> (D4052) Kg/L	0.85
<b>POUR POINT (°C)</b> (D97)	-33
<b>FLASH POINT (°C)</b> (D92)	65

## Sizes & Order Codes

Size	Form Oil
<b>18.9L Pail / 5 US Gal</b>	FU0016540
<b>205L Metal /54.2 US Gal</b>	FU0016550
<b>1000L/264 US Gal</b>	FU0016560
<b>Bulk Tote</b>	FU0016501

**Form Oil** is a blend of quality pure paraffinic base oil and petroleum distillate and is used as a form-release agent with a rust-preventive coating.

**Form Oil** works with concrete form-work coated with this oil before being filled with concrete.

**Form Oil's** viscosity allows it to be sprayed or brushed on and the light color won't stain the concrete. A fatty material added to the formula reacts with the alkali in the cement to form a barrier between the form and the cement that helps them to separate easily and leaves the concrete with a smooth surface. This also protects wood forms from tearing and reduces the maintenance time needed to remove dried concrete from the form surface.

**Form Oil** as a coating helps prevent steel forms and machinery from rusting and prevents wood forms from absorbing water and rotting.



[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants)  
1.800.574.5823

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to September 28, 2022.

[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants) 1.800.574.5823