# **2-Cycle Plus**Two-Stroke Engine Oil



#### **Features & Benefits**

- Superior deposit control, extends spark plug life
- Excellent rust and corrosion protection
- Certified to the highest NMMA® performance standard TC-W3®
- · Ashless formulation
- Suitable for premix and oil injection systems
- Specially formulated for outboards and other liquid cooled 2-stroke engines
- Suitable for use in all 2-T DFI (Dual Fuel Injected)
- Outboard engines ex. E-Tec, Opitmax, HPDI etc.

### **Specifications**

✓ Meets Requirements • Licensed

Specification	2-Cycle Plus
NMMA TC-W3 <sup>®</sup> (Certificate No. RL40462F)	•
API TC	✓
JASO FB	✓

## **Typical Results**

Test Method	2-Cycle Plus
VISCOSITY (D445) cSt @ 40 °C cSt @ 100 °C	27.6 6.2
VISCOSITY INDEX (D2270)	185
<b>DENSITY @ 15 °C</b> (kg/L) (D4052)	0.87
POUR POINT (°C) (D97)	-48
FLASH POINT (°C) (D93)	55

#### Sizes & Order Codes

Size	2-Cycle Plus
946 ml/1 US Qt	F0000115



**2-CYCLE Plus** is a premium lubricant for water-cooled outboard 2-stroke gasoline engines. This formulation was designed to ensure low carbon, ashless performance, and improved ease of mixing with gasoline.

**2-CYCLE Plus** is suitable for both premixed and modern oil injection systems. With its distinctive blue color, you will have positive confirmation that the oil has been pre-mixed into the gasoline. The ashless formulation provides for clean pistons and cylinders while minimizing deposits that can cause ring-sticking, portplugging, and pre-ignition. It also effectively prevents rust and corrosion, which is very important in the humid environment of outboard engines.

2-CYCLE Plus is recommended wherever the manufacturer recommends an NMMA® approved lubricant, meeting the current performance standard for such oils, TC-W3®. Engine manufacturers have shown that this oil, when compared to oils of the previous TC-W2 category, doubles the life of the powerhead.



www.irvingoil.com/lubricants 1.800.574.5823

www.irvingoil.com/lubricants 1.800.574.5823