

Marine DEF

Marine Grade Diesel Exhaust Fluid



Features & Benefits

- Meets ISO 18611-1:2014
- Non-toxic, non-polluting, non-hazardous and non-flammable
- Reduces harmful emissions
- Increases fuel efficiency

Typical Results

| Test | Units | Typical | Min | Max |
|--------------------------|---------|------------------------|---------------------|---------------------|
| Urea Content | % (m/m) | 40.1 | 39.0 | 41.0 |
| Density at 20°C | kg/L | 1.1142 | 1.050 | 1.177 |
| Refractive Index at 20°C | - | 1.3958 | 1.3934 ¹ | 1.3982 ² |
| Alkalinity (as Ammonia) | % (m/m) | <0.1 | - | 0.5 |
| Biuret | % (m/m) | 0.3 | - | 0.8 |
| Aldehydes | mg/kg | 1.3 | - | 100 |
| Insoluble matter | mg/kg | 2.6 | - | 50 |
| Phosphates | mg/kg | 0.3 | - | 1 |
| Calcium | mg/kg | <0.1 | - | 1 |
| Iron | mg/kg | <0.1 | - | 1 |
| Copper | mg/kg | <0.1 | - | 1 |
| Zinc | mg/kg | <0.1 | - | 1 |
| Chromium | mg/kg | <0.1 | - | 1 |
| Nickel | mg/kg | <0.1 | - | 1 |
| Aluminum | mg/kg | <0.1 | - | 1 |
| Magnesium | mg/kg | <0.1 | - | 1 |
| Sodium | mg/kg | <0.1 | - | 1 |
| Potassium | mg/kg | <0.1 | - | 1 |
| Identity (FTIR) | - | Identical to reference | - | - |

¹ Minimum Refractive Index based on 0.0% Biuret
² Maximum Refractive Index based on 0.8% Biuret

IRVING MARINE DEF (Diesel Exhaust Fluid) is a 40% Aqueous Urea Solution (AUS 40) manufactured with high purity urea mixed with quality electro deionized (EDI) water designed to meet the specifications of ISO 18611-1:2014 for NO_x emissions of large diesel engines on ships.

IRVING MARINE DEF is produced to exceed the quality characteristics defined in ISO 18611-1. Typical results of the contaminants analysed are far lower than the maximum set out by the ISO standard. Typical results are within the stringent quality specification outlined in ISO 22241-1:2019 for DEF contaminants.

IRVING MARINE DEF is certified as a Marine Diesel Exhaust Fluid by the American Petroleum Institute.

Sizes & Order Codes

| Size | Code |
|------|----------|
| Bulk | B0103101 |

www.irvingoil.com/lubricants
1.800.574.5823

Marine DEF

Marine Grade Diesel Exhaust Fluid

ISO 18611-3:2014 - Shelf Life as a Function of Storage Temperature

| Constant Ambient Storage Temperature (°C) | Minimum Shelf Life (Months) |
|---|---|
| 0 – 25 | 18 |
| <30 | 12 |
| <35 | 6 |
| >35 | Possible significant loss of shelf life: check every batch before use |

NOTE: The main factors taken into account to define the shelf life in this table are the ambient storage temperature and the initial alkalinity of AUS 40. The difference in evaporation between vented and non-vented storage containers is an additional factor.

Never store Marine DEF in direct sunlight.

Table Reference:

International Organization for Standardization. (2014). Ships and marine technology – Marine NOx reduction agent AUS 40 – Part 3: Handling, transportation, and storage (ISO Standard No. 18611-3:2014). Retrieved from <https://www.iso.org/obp/ui/#iso:std:iso:18611:-3:ed-1:v1:en>

Always consult your owner's manual for verification of fluid type and grade!

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals.

Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to July 4, 2022.

www.irvingoil.com/lubricants 1.800.574.5823