



TRANSflo CVT

Continuously Variable Transmission Fluid



Features & Benefits

- Provides robust, durable performance
- Performance validated with extensive vehicle testing
- Extends integrity and operational life of critical components
- Anti-shudder durability and friction protection

Specifications

Suitable For Use:	
Audi Multitronic	Mitsubishi CVTF ECO J4
Chery CVT	Mitsubishi (DiaQueen) CVTF J1
Daihatsu AMMIX CVTF-DC	Mitsubishi (DiaQueen) CVTF J4 & J4+
Daihatsu AMMIX CVTF-DFC	Nissan N-CVT, NS-1, NS-2, NS-2V & NS-3
Daihatsu AMMIX CVTF-DFE	Punch CVTF-EX1
Daihatsu Fluid TC	Renault CVT CK/SK/FK
Dodge/Chrysler/Jeep/Mopar CVT+4®	Renault Elf Matic CVT
Dodge/Jeep/Chrysler NS-2	Subaru ECVT
Fiat Tutela Car CVT N.G	Subaru iCVT & iCVT FG
Fujijyuuko i-CVTF FG	Subaru Lineartronic chain CVT, CVT II; High Torque (HT) CVTF & CV-30
GM/Saturn DEX-CVT, GM 1940713 & 1940714	Subaru NS-2
Honda CVT, HMMF, & Z-1 ¹	Suzuki CVTF Green 1 (Shell Green 1V)
Honda HCF2	Suzuki CVTF Green 2
Hyundai/Kia SP CVT-1	Suzuki CVTF 3320 & 4401
Hyundai/Kia SP III ²	Suzuki CVTF TC
Idemitsu CVTF-EX1	Suzuki NS-2
Lexus Fluid TC, Fluid FE	Toyota CVTF FE & TC
Mazda CVTF 3320	Volvo CVT 4959
MG Rover EM-CVT	VW/Audi TL 52516 (G 052 516)
Mini Cooper (BMW) EZL 799, EZL 779A & ZF CVT V1	VW/Audi TL 52180 (G 052 180 A2)
Mitsubishi (DiaQueen) ATF SP-III ²	Zoty CVTs

Electro Mobility Suitable For Use:
Toyota THSII / Toyota Prius
Ford Escape Hybrid with e-CVT
Honda iMMD
Jatco CVT 8 Hybrid

¹ CVT without starting clutch
² CVT model only
 Suitable For Use (SFU) - Supporting data from field trial studies to demonstrate acceptable performance
 CVTF – Continuously Variable Transmission Fluid

TRANSflo CVT is a synthetic transmission fluid designed for use in Continuously Variable Transmissions. This multi-vehicle CVT fluid provides excellent anti-shudder durability and friction protection to keep your transmission running smoothly.

TRANSflo CVT fluid meets the performance requirements of a wide variety of vehicles equipped with push-belt and chain CVT's, such as Nissan, Toyota, Subaru, Mitsubishi, Suzuki, and Honda.

TRANSflo CVT is not to be used in DCT applications.

Typical Results

Test Method	TRANSflo CVT
COLOUR (Visual)	GREEN
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	33.3 7.1
VISCOSITY INDEX (D2270)	185
DENSITY @ 15 °C (D4052) (kg/L)	0.847
BROOKFIELD VISCOSITY (D2983) cP @ -40°C	14,900
POUR POINT (°C) (D97)	-51
FLASH POINT (°C) (D93)	197

Sizes & Order Codes

Size	Order Codes
946 ml/ 1 US Qt.	F0126015
Bulk	B0124801



www.irvingoil.com/lubricants
1.800.574.5823

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 21-06-22.
<http://www.irvingoil.com/lubricants> **1.800.574.5823**