



# TRANSflo

## Automatic Transmission Fluid



### Features & Benefits

- Excellent corrosion and foam prevention
- Safe for all seals
- Promotes transmission cleanliness

### Specifications

✓ Meets Requirements

| Specification  | TRANSflo |
|--|----------|
| Allison C-3, C-4   | ✓        |
| Allison TES-389  | ✓        |
| American Motors ATF +3 (MS 7176-E)                               | ✓        |
| Audi 5HP LT71141   | ✓        |
| Audi G 052 162-A1/A2 (ZF Lifeguard 5)                            | ✓        |
| BMW 7045E, ETL-8072B, LA2634                                     | ✓        |
| CAT TO-2   | ✓        |
| Chrysler ATF+2, +3   | ✓        |
| Ford MERCON®   | ✓        |
| Ford WSS M2C 138CJ, 166H   | ✓        |
| GM DEXRON® II, IID, IIE, IIIG, IIH                               | ✓        |
| GM TASA  | ✓        |
| Hyundai/Kia DEX-II/SP-II   | ✓        |
| Jaguar JLM 20292, 20238  | ✓        |
| Mazda ATF M-III, & F-I   | ✓        |
| MB ZF 4HP20  | ✓        |
| NAG 1 (Chrysler, Jeep, Cherokee)                                 | ✓        |
| Opel/GM 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466       | ✓        |
| Peugot/Citreon Z 000169756, AL4 Automatic gearbox oil (#9730.AE) | ✓        |
| Porsche 000 043 205 09, 999 917 547 00, Z 000169756              | ✓        |
| Renault Matic D2, DPO/AL4  | ✓        |
| Volvo CE 97340   | ✓        |
| Volvo 97325 & 97335  | ✓        |
| Vickers M2950-S, I-286-S   | ✓        |
| VW G US 000 162  | ✓        |
| ZF TE-ML 05L, 09, 21L  | ✓        |

### Typical Results

| Test Method                   | TRANSflo |
|-------------------------------|----------|
| COLOUR                        | RED      |
| VISCOSITY (D445)              |          |
| cSt @ 40°C                    | 33.2     |
| cSt @ 100°C                   | 7.1      |
| VISCOSITY INDEX (D2270)       | 186      |
| POUR POINT (D97) (°C)         | -42      |
| FLASH POINT (D93) (°C)        | 190      |
| DENSITY @ 15°C (D4052) (kg/L) | 0.85     |

**TRANSflo** is a premium product specially formulated for automatic transmissions manufactured in 2005 and earlier for General Motors, Ford, and Chrysler vehicles.

**TRANSflo** provides excellent low-temperature fluidity and maintains its film-thickness at temperatures over 149°C for bearing and gear lubrication.

**TRANSflo** meets specifications by Allison as a type C-4 fluid and can be used in Ford model C-6 automatic transmissions built on or after 1977.

**TRANSflo** can also be used in certain power steering, hydro-static systems and power-shift transmissions where this type of oil is recommended.

**TRANSflo** may also be used as hydraulic fluid due to its excellent low-temperature fluidity and red colour.

### Sizes & Order Codes

| Size                    | TRANSflo |
|-------------------------|----------|
| 946mL / 1 US Qt         | F0020815 |
| 3.78L / 1 US gal        | F0020826 |
| 18.9L / 5 US gal Pail   | F0082240 |
| 205L / 54.2 US gal Drum | F0015650 |
| 1000L / 264 US gal Tote | F0020860 |
| Bulk                    | B0020801 |

[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants)  
1.800.574.5823

Always consult your owner's manual for verification of fluid type and grade!

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals.

Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to October 3<sup>rd</sup> 2022.

[www.irvingoil.com/lubricants](http://www.irvingoil.com/lubricants) 1.800.574.5823