

Tractor Hydraulic High Performance Fluid

Features & Benefits

- Superior load carrying and wear protection
- Excellent foam resistant properties
- Exceptional yellow-metal protection
- Shear stable
- · Excellent frictional characteristics
- · Superior fluidity at low temperatures
- Three formulations to suit your equipment's needs

Typical Results

Test Method	THF	THF Premium	THF (W)
ASTM COLOUR (D1500)	2.0	2.0	2.0
DENSITY @ 15°C (D4052) (kg/L)	0.86	0.86	0.85
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	59.4 9.5	46.4 9.5	38.8 7.5
VISCOSITY INDEX (D2270)	141	196	165
POUR POINT (D97) (°C)	-42	-64	-50
FLASH POINT (D93) (°C)	212	201	185
KRL SHEAR TEST after 20 hrs VISCOSITY cSt @ 100°C (D445)	8.8	7.8	7.0
BROOKFIELD VISCOSITY (D2983) (cP) @-20°C @-35°C @-40°C	3,820 28,850 71,600	1,365 - 18,500	- - 16,800
FOAM TEST (D892) (Tendency mL / Stability mL) Sequence I Sequence II Sequence III	0/0 10/0 0/0	0/0 30/0 0/0	0/0 30/0 0/0

Sizes & Order Codes

Size	THF	THF Premium	THF (W)	
3.78 L / 1 US Gal	-	F0020426	-	
18.9 L / 5 US Gal	F0079440	F0086140	F0079340	
205 L / 54 US Gal	F0060850	F0015550	-	
1000 L / 264 US Gal	F0060860	F0020460	-	
1000L / 264 US Gal Bulk Tote	F0108301	F0109101	-	
BULK	B0060801	B0020401	B0060001	



Tractor Hydraulic Fluids are Universal Tractor Transmission Oils (UTTO) that are formulated for use in transmissions, final drives, power take-off, wet brakes, hydraulics, clutches, and power steering systems. Designed for use in agricultural, construction, and mining equipment that uses a common fluid reservoir.

Tractor Hydraulic Fluid is available in three different grades:

- THF is made with high quality group II base oils and recommend for summer operation, but also suitable for year round use where temperatures are above -25°C.
- THF Premium is full synthetic and a true "all season" fluid that is suitable in both hot and cold temperatures.
- THF (W) is made with high quality group II/II+ base oils and formulated for extra protection in the cold winter months. Meeting the requirements of J20D.

Tractor Hydraulic Fluids act as a universal hydraulic oil that protects against wear and prevents bronze transfer in piston pumps to prevent loss of efficiency.

Tractor Hydraulic Fluid's frictional characteristics prevent stick/slip problems and reduce brake noise/chatter. They also have superior fluidity at low temperatures with pour points as low as -42°C (THF), -64°C (THF Premium) and -50°C (THF W).

Tractor Hydraulic Fluids are not to be used in STOU engine applications.



www.irvingoil.com/lubricants 1.800.574.5823

Tractor Hydraulic High Performance Fluid



Specifications

✓ Meets Requirements

Specifications	THF	THF Premium	THF (W)
AGCO 821XL	✓	✓	-
Allison C2, C3 & C4	✓	✓	-
API GL-4	✓	✓	✓
Caterpillar TO-2	✓	✓	✓
CNH MAT 3505	✓	1	-
CNH MAT 3510	✓	✓	-
CNH MAT 3525	✓	✓	-
Dennison HF-0. HF-1, HF-2 (except demulsibility)	*	*	-
Deutz-Allis Power Fluid 821XL, 25741, 25743, 246634, 272843	✓	✓	-
Dresser	✓	✓	-
Fiat Heston AF-87	✓	✓	-
Ford FNHA-2-C-200 & 201	✓	✓	-
Ford ESN-M2C-41, 41A & B, & 43	✓	✓	-
Ford ESN-M2C-48 B & C	*	✓	1
Ford ESN-M2C53 A & B	*	✓	-
Ford ESN-M2C-77A, 78A, 79A	\	✓	1
Ford ESN-M2C-86 A-C	\	✓	1
Ford ESN-M2C-92A	\	✓	1
Ford ESN-M2C134A-D (NH-410B)	\	✓	1
Ford ESN-M2C-142A & 143	\	✓	•
Ford ESN-M2C-159 A-C	\	✓	1
Ford M2CA-C	✓	✓	1
Ford New Holland M4864A & B	\	✓	ı
Industry of Machinery and Tractors (IMT)	\	✓	1
International Harvester Hy-Tran B-6	\	✓	1
Japanese Construction Mechanization Association (JCMAS), HK P-041 & P-042	*	✓	
J.I. Case Case-O-Matic Type A	✓	✓	-
JI Case MS-143, 144, 145 International Famall (TCH Fluid)	✓	✓	-
JI Case MS-185 (TFD Fluid)	✓	✓	-
JI Case MS-1204-1205 (Powergard PFT)	✓	✓	-
JI Case MS-1206 (Powergard PFT)	✓	✓	-
JI Case MS-1207	✓	✓	-
JI Case MS-1209 (HyTran Ultra or MultiTran)	✓	✓	-
JI Case MS-1210	✓	✓	✓
JI Case MS-1216	✓	✓	-
JI Case MS-1230 (Poclain Equipment)	✓	✓	-
JI Case MS-1317	*	✓	-

Specifications	THF	THF Premium	THF (W)
John Deere J20A, J20B, J20C, J14A-C & J21A	✓	✓	-
John Deere J20D	-	✓	✓
Kioti	✓	✓	-
Komatsu KES 07.866, AXO80	✓	✓	-
Komatsu-Dresser B06.0002	✓	✓	-
Kubota UDT	✓	✓	-
Kubota Super UDT & UDT2	-	✓	-
Landini	✓	✓	-
MF M1103A & B	✓	✓	-
MF 1127, 1127 A&B	✓	✓	-
MF M1110	✓	1	-
MF M1129, M1129A (Permatran)	✓	✓	-
MF M1135 (Permatran III)	✓	✓	-
MF M1138	✓	1	-
MF M1139 (UTTO Only)	✓	✓	-
MF M1141	-	1	-
MF M1143	✓	✓	-
MF M1144 (UTTO Only)	✓	✓	-
MF M1145	✓	1	-
Parker (Denison UTTO) HF-0, HF-1 & HF-2	✓	✓	-
Quatrol	✓	✓	-
Renk-Doromat 87.3 & 874A/B	✓	✓	-
Sauer Sunstrand/Danfoss & Hydro Static Trans Fluid	✓	✓	-
Sperry Vickers/Eaton I-286S Industrial Hydraulics	✓	✓	-
Sperry Vickers/Eaton M2950S Mobil Hydraulics	✓	✓	-
Steiger HTF (SEMS 17001)	✓	✓	-
Valmet	✓	✓	-
Valtractores	✓	✓	-
Valtra G2-08 & G2-B10	✓	✓	-
Versatile Gear & HydrTrans Fluid	✓	✓	-
Vickers 35VQ25	✓	✓	✓
Volvo WB101 (VCE97303), except for motor grader rear axle	✓	✓	-
Volvo VCE 1273.03	✓	✓	-
Wet brake applications	✓	✓	-
White/Minneapolis-Moline/Oliver/ New Idea 55, 5J, Q-1705, Q-1722, Q-1766, Q-1766B, Q-1802, Q-1826	✓	*	-
Yanmar	✓	✓	-
2214 6 2414	/		

23M & 24M