



TRANSflo CVT

Continuously Variable Transmission Fluid

Features & benefits

- Provides robust, durable performance
- Performance validated with extensive vehicle testing
- Extends integrity and operational life of critical components
- Anti-shudder durability and friction protection



Specifications

■ Suitable for use

Specification	TRANSflo CVT
Audi Multitronic	■
Chery CVT	■
Daihatsu AMMIX CVTF-DC, CVTF-DFC, CVTF-DFE	■
Daihatsu Fluid TC	■
Dodge/Chrysler/Jeep/Mopar CVT+4®	■
Dodge/Jeep/Chrysler NS-2	■
Fiat Tutela Car CVT N.G	■
Fujijyuuko i-CVTF FG	■
GM/Saturn DEX-CVT, GM 1940713 & 1940714	■
Honda CVT, HMMF, & Z-1 ¹	■
Honda HCF-2	■
Hyundai/Kia SP CVT-1, SP III ²	■
Idemitsu CVTF-EX1	■
Lexus Fluid TC, FE	■
Mazda CVTF 3320	■
MG Rover EM-CVT	■
Mini Cooper (BMW) EZL 799, EZL 779A & ZF CVT V1	■
Mitsubishi (DiaQueen) ATF SP-III ²	■
Mitsubishi CVTF ECO J4	■
Mitsubishi (DiaQueen) CVTF J1, J4, J4+	■
Nissan N-CVT, NS-1, NS-2, NS-2V & NS-3	■
Punch CVTF-EX1	■
Renault CVT CK/SK/FK	■
Renault Elf Matic CVT	■
Subaru ECVT, iCVT, iCVT FG	■
Subaru Lineartronic chain CVT, CVT II; High Torque (HT) CVTF & CV-30	■
Subaru NS-2	■
Suzuki CVTF Green 1 (Shell Green 1V), Green 2	■
Suzuki CVTF 3320, 4401, TC	■
Suzuki NS-2	■
Toyota CVTF FE, TC	■
Volvo CVT 4959	■
VW/Audi TL 52516 (G 052 516), 52180 (G 052 180 A2)	■
Zotye CVTs	■

¹ CVT without starting clutch

² CVT model only

TRANSflo CVT is a synthetic transmission fluid designed for continuous variable transmission. This multi-vehicle CVT fluid provides excellent anti-shudder durability and friction protection to keep your transmission running smoothly.

TRANSflo CVT fluid meets the performance requirements of vehicles equipped with push-belt and chain CVTs, such as Nissan, Toyota, Subaru, Mitsubishi, Suzuki, and Honda.

TRANSflo CVT is not to be used in DCT applications.

Specifications Continued

Specification	TRANSflo CVT
Toyota THSII / Toyota Prius	■
Ford Escape Hybrid with e-CVT	■
Honda iMMD	■
Jatco CVT 8 Hybrid	■
Mazda SKYACTIVE-HYBRID	■
Toyota THSII / Toyota Prius	■

Typical results

Test Method	TRANSflo CVT
VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	33.3 7.1
VISCOSITY INDEX (D2270)	185
COLOUR	Green
DENSITY @ 15°C (D4052), kg/L	0.847
POUR POINT (D97), °C	-51
FLASH POINT (D93), °C	197
BROOKFIELD @ -40°C (D2983), cP	14,000

Sizes & order codes

Size	TRANSflo CVT
946 mL (1 US QT)	F0126015
Bulk	B0124801

Always consult your owner's manual for verification of fluid type and grade.
Check with sales associate for the latest product approvals and acceptable performance data.
Please note these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to November 8, 2024.

www.irvingoil.com/lubricants • 1.800.574.5823